

BGA Heat Sink - High Performance maxiFLOW/superGRIP



ATS Part#: **ATS-X50330G-C1-R0**
 Description: 33.00 x 33.00 x 12.50 mm BGA Heat Sink - High Performance maxiFLOW/superGRIP



Heat Sink Type: **maxiFLOW**
 Heat Sink Attachment: **superGRIP**
 Equivalent Part Number: **N/A**

**Image above is for illustration purpose only.*

Features & Benefits

- Designed for 33 x 33 mm components
- Requires minimal space around the component's perimeter; ideal for densely populated PCBs
- Allows the heat sink to be detached and reattached without damaging the component or the PCB, an important feature in the event a PCB may need to be reworked
- Strong, uniform attachment force helps achieve maximum performance from phase-changing TIMs
- Eliminates the need to drill mounting holes in the PCB

Thermal Performance

| AIR VELOCITY | | @200 LFM 1.0 M/S | @300 LFM 1.5 M/S | @400 LFM 2.0 M/S | @500 LFM 2.5 M/S | @600 LFM 3.0 M/S | @700 LFM 3.5 M/S | @800 LFM 4.0 M/S |
|--------------------|---------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| THERMAL RESISTANCE | Unducted Flow | 3.5 °C/W | 2.8 °C/W | 2.4 °C/W | 2.1 °C/W | 2 °C/W | 1.8 °C/W | 1.7 °C/W |
| | Ducted Flow | 2.7 | N/A | N/A | N/A | N/A | N/A | N/A |

Product Detail

| Schematic Image | Dimension A | Dimension B | Dimension C | Dimension D | TIM | Finish |
|--|-------------|-------------|-------------|-------------|------|---------------|
| <p><i>*Image above is for illustration purpose only.</i></p> | 33.00 mm | 33.00 mm | 12.50 mm | 58.2 mm | T766 | BLUE-ANODIZED |
| <p>Notes:</p> <ul style="list-style-type: none"> • Dimension A and B refer to component size. • Dimension C is the heat sink height from the bottom of the base to the top of the fin field. • Thermal performance data are provided for reference only. Actual performance may vary by application. • ATS reserves the right to update or change its products without notice to improve the design or performance. • ATS certifies that this heat sink assembly is RoHS-6 and REACH compliant. • Contact ATS to learn about custom options available. | | | | | | |

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.

© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA



ATS ADVANCED
THERMAL
SOLUTIONS, INC.
Innovations in Thermal Management®