	τ <u>ο</u> .	m m		0			
Skelig Shown as example Standard Harder Shell Material Shell Sheron Shell Sheron Material Shell Sheron							
CHARACTERISTICS Standard : Based on MIL DTL 38999 Series II Sile Material Muminium Shell Material Muminium Shell Plating Eldac Zinc Nickel -insulator Time moglastic -contacts connector dimension Seals & Grommet Silcion Elastomer -contact Plating Gold ever copper Alley 0.8µm minimum -ourability Sold Waiting cycles -Bell Plating Sold Vaiting cycles -Dorability Sold Nating cycles -Bell Plating Sold Vaiting cycles -Dorability Sold Nating cycles -Bell Plating Sold Contact -Basic Serieles: 80 11 SHELL TYPE: Plug with RFI Shielding Contact Later CONTACT TYPE: Sind Crimp Contact Processent Hop repression SHELL TYPE: Sind Crimp Contact Processent Hop repression SHELL TYPE: Sind Accessories NPROS / PROJECT -represent lineor NPROS / PROJECT Sold First Release Sold Series: 80 11 2 05 N Shell TYPE: Plag				LAYOUT SHOWN AS EXAM	IPLE		
-Standard : Based on MIL-DTL-38999 Series III Shell Material : Aluminium Shell Material : Aluminium Shell Plating :: Black Zinc Nickel -Insulator :: Copper Alloy -Sourceut minimum :: Copper Alloy -Sourable & Growmed :: Slicon Elastomer -Contacts :: Copper Alloy -Sourable With Souriau contacts and Accessories :: Contact is sued by ether of the Parties of the Par		Keying Shown as example					
Standard : Based on MIL-DTL-38999 Series III Shell Matchal : Aluminium Shell Plating : Black Zinc Nickel -insulator : Thermoplastic -Contacts : Copper Alloy -Seek & Grommet : Silicon Elastomer -Ourability : S00 Mating cycles -Derivered with Souriau contacts and Accessories : -Temperature Range : -65°C to +175°C -Sait Spray : : : : : : : : : : : : : : : : : : :	CHARACTERISTICS	Connector dimension					
Shell Matchal ∴ Aluminium Shell Matchal ∴ Aluminium Shell Plating ∷ Aluminium Shell Plating ∷ Contacts · Shell Plating : Contacts · Contacts : Copper Alloy · Seale & Grommet : Silicon Elastomer · Contact Sing : Sold over copper Alloy Bug Ngµm minimum · Ourability : Sold over copper Alloy Bµm minimum · Ourability : Sold over copper Alloy Bµm minimum · Ourability : Sold over copper Alloy Bµm minimum · Ourability : Sold over copper Alloy Bµm minimum · Ourability : Sold over copper Alloy Bµm minimum · Ourability : Sold over copper Alloy Bµm minimum · Ourability : Sold over copper Alloy Bµm minimum · Ourability : Sold over copper Alloy Bµm minimum · Ourability : Sold over copper Alloy Bµm minimum · Ourability : Sold over copper Alloy Bµm minimum · All Ballo 2016 : Sold Strate · All Ballo 2016 : Sold Strate · Mass : 14.83 g ± 10% Basic Strates: BD · Sold Strate : Sold Strate · Sol	-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal					
- Shell Plating - Black Zinc Nickel - Insulator - ThermoplasticContact Plating - Contact - Contact Plating - Contact - Contac	-Shell Material : Aluminium			SOURIAU shall not be liable for any no	n-conformity or damage		
Instantion Intermediation -Contact ::Comper Alley -Seals & Grommet :Silicon Elastomer -Contact Plating ::Gold over copper Alley 0.8µm minimum -Derivered with Souriau contacts and Accessories PN: 8D511Z05AB -Temperature Range ::Go't to +175° C -Sait Spray :S00 hours -Mass :14.83 g ± 10% Basic SERIES: 8D SHELL TYPE :Sundard Crimp Contact SHELL TYPE :Sundard Crimp Contact PLATING :Z PLATING :Z				due to a use of the Products which does not comply with			
Contacts : Copper Alloy -Seals & Grommet : Sillicon Elastomer Contact Plaing : Gold over copper Alloy 0.8µm minimum Durability : Sold nours Temperature Range : - 65°C to +175°C Sait Spray : Sold nours Mass : 14.83 g ± 10% Basic SerileS: 8D SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SZE : 11 CONTACT TYPE : Standard Crimp Contact PLATING : Z Black Zinc Nickel CONTACT LAYOUT : 11-05							
- Contact Plating ::::::::::::::::::::::::::::::::::::							
-Durability :: 500 Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range :: 65'C to +175'C -salt Spray :: 500 hours -Mass :: 14.83 g ± 10% BASIC SERIES: 8D SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL TYPE : Standard Crimp Contact SHELL SIZE : 11 ORIENTATION : B PLATING : Z PLATING : Z				Country]	
-Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +175°C -Salt Spray : 500 hours -Mass : 14.83 g ± 10% BASIC SERIES: 8D 5 - 11 Z 05 A B CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 PLATING : Z = Black Zinc Nickel PN: 8D511Z05AB A 18-10-2016 First Release CONTACT TYPE : Plug with RFI Shielding CONTACT TYPE : Plug with RFI Shielding PLATING : Z = Black Zinc Nickel PN: 8D511Z05AB A 18-10-2016 First Release CONTACT TYPE : Plug with RFI Shielding CONTACT TYPE : Plug with RFI Shielding CONTACT TYPE : Plug with RFI Shielding PLATING : Z = Black Zinc Nickel PN: 8D511Z05AB A 18-10-2016 First Release CONTACT TYPE : Plug with RFI Shielding CONTACT TYPE : Plug with RFI Shielding CONTACT TYPE : Plug Stone Contact CONTACT TYPE : Plug Stone Contact SOURIAU CONTACT TYPE : Plug Stone Contact CONTACT TYPE : Plug Stone Contact CONTA			Γ				
-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours -Mass : 14.83 g ± 10% BASIC SERIES: 8D 5 - 11 Z 05 A B CONTACT TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 PLATING : Z = Black Zinc Nickel CONTACT TYPE : PIN(500 Matings) PLATING : Z = Black Zinc Nickel CONTACT TYPE : PIN(500 Matings) PLATING : Z = Black Zinc Nickel CONTACT TYPE : PIN(500 Matings) PLATING : Z = Black Zinc Nickel CONTACT TYPE : PIN(500 Matings) PLATING : Z = Black Zinc Nickel CONTACT TYPE : PIN(500 Matings) CONTACT TYPE : PIN					540		
-Salt Spray :: 500 hours -Mass :: 14.83 g ± 10% A 18-10-2016 First Release -Mass :: 14.83 g ± 10% A 18-10-2016 First Release -MOD N ^e Designed By: Date: CUSTOMER DRAWING Designed By: Date: CUSTOMER DRAWING Designed By: Date: CUSTOMER DRAWING Designed By: Date: CUSTOMER DRAWING SALE Aluminium Plug 8D series SCALE Aluminium Plug 8D series	-Delivered with Souriau contacts and Accessories			FIN. OD311203			
-Salt Spray : 500 hours -Mass : 14.83 g ± 10% BASIC SERIES: <u>8D</u> 5 - 11 Z 05 A B <u>SHELL SIZE : 11</u> PLATING : Z = Black Zinc Nickel <u>CONTACT TYPE : PIN(500 Matings)</u> PLATING : Z = Black Zinc Nickel <u>SOURIAU DRG N°</u> <u>SHEET</u>	-Temperature Range65°C to +175°C		A 10 10 2010	First Polocco			
Designed By: Date: CUSTOMER DRAWING Designed By: Date: CUSTOMER DRAWING BASIC SERIES: 8D 5 - 11 Z 05 A B Intervention SCALE Aluminium Plug 8D series SHELL TYPE : Plug with RFI Shielding - 11 Z 05 A B ORIENTATION : B SCALE NPRDS / PROJECT 859 CONTACT TYPE : Standard Crimp Contact ORIENTATION : B CONTACT TYPE : PIN(500 Matings) SOURIAU This document is the property of SOURIAU SOURIAU This document is the property of SOURIAU SOURIAU it must not be reproduced or communicated without permission PLATING : Z = Black Zinc Nickel CONTACT TYPE : PIN(500 Matings) FORMAT SOURIAU DRG N° SHEET	-Salt Spray : 500 hours						
BASIC SERIES: 8D 5 - 11 Z 05 A B SHELL TYPE : Plug with RFI Shielding 0RIENTATION : B SCALE General linear NPRDS / PROJECT CONTACT TYPE : Standard Crimp Contact 0RIENTATION : B XA B This document is the property of SOURIAU SHELL SIZE : 11 CONTACT TYPE : PIN(500 Matings) CONTACT TYPE : PIN(500 Matings) WWW.SOURIAU.COM This document is the property of SOURIAU PLATING : Z = Black Zinc Nickel CONTACT TYPE : PIN(500 Matings) CONTACT LAYOUT : 11-05 SOURIAU SOURIAU DRG N°	-Mass : 14.83 g ± 10%					MOD N°	
BASIC SERIES: 8D 5 11 Z 05 A B SCALE General linear Tolerances: ±- NRDS / PROJECT SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact ORIENTATION : B NA Image: Contact Type : Plug with RFI Shielding This document is the property of SOURIAU SHELL SIZE : 11 CONTACT TYPE : Plug Standard Crimp Contact CONTACT TYPE : PIN(500 Matings) CONTACT TYPE : PIN(500 Matings) This document is the property of SOURIAU PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 11-05 FORMAT SOURIAU DRG N° SHEET							
BASIC SERIES. ab 3 4 1 2 03 A B A B Tolerances: B Tolerances: B B Tolerances: B <th< td=""><td></td><td></td><td>IIILE</td><td>Aluminiur</td><td>n riug ad series</td><td></td></th<>			IIILE	Aluminiur	n riug ad series		
SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 11-05 Format Tolerances: ± NA NB NA NA Tolerances: Tolera	BASIC SERIES: 8D 5 - 11 Z 05	АВ	SCALE		NPRDS / PROJECT		
CONTACT TYPE : Standard Crimp Contact ORIENTATION : B SHELL SIZE : 11 CONTACT TYPE : PIN(500 Matings) PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 11-05 FORMAT SOURIAU This document is the property of SOURIAU SOURIAU SOURIAU	SHELL TYPE : Plug with RFI Shielding		NA		859		
SHELL SIZE : 11 CONTACT TYPE : PIN(500 Matings) SOURIAD WWW.SOURIAD.COIM it must not be reproduced or communicated without permission PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 11-05 FORMAT SOURIAU DRG N° SHEET			_	· · · ·		perty of	
PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 11-05 FORMAT SOURIAU DRG N° SHEET			- SOURIAU	WWW.SOURIAU.COM	VI it must not be reproduc		
	SHELL SIZE : 11		—				
A3 8D511Z05AB-C 1/2	PLATING : Z = Black Zinc Nickel	CONTACT LAYOUT : 11-0					
			A3	8D511Z05	AB-C	1/2	

-	Ŧ	۵	וד	m		0
		Contact Layout				
4	-x	$ \begin{array}{c} \bullet \\ \bullet $				
	Shell Arrangement Numb size no.	+.065 (1.65) +.056 (1.42) +.113 (2.87) 065 (1.65) +.000 (0.00) 130 (3.30) 112 (2.87) 065 (1.65) 065 (1.65) +.056 (1.42)				
ω	<u>11</u> -5 5					
	-					SOURIAU shall not be liable for due to a use of the Products the Specifications issued by eithe (professional recommen
N						Cou F PN: 8D51
					A 18-10-20 ISS DATE Designed By:	116 First Release
-					TITLE SCALE NA	Alum General linea Tolerances:
					SOURIA	
					FORMAT A3	SOURIA 8D511
L	Н	G	F	E	D	C

