	T	۵	т		m			0	
4		V Thread	ØF						
ω								LAYOUT S	SHOWN AS EXAI
			Keying Shoy	wn as example					
	CHARACTERISTICS		Keying Show			-			
	-Standard : Based on MIL-DTL-3899	9 Series III		Connector Dim	Nominal				
	-Shell Material: Aluminiur-Shell Plating: Olive drab-Insulator: Thermopl-Contacts: Copper Al	o Cadmium astic Iloy		F Z VV THREAD	30.15 Max 31.5 Max M25x1-6g	-		SOURIAU shall not be due to a use of the the Specifications issued (professional re	Products which d by either of th
N	-Seals & Grommet : Silicon Ela -Contact Plating : Gold over	istomer · copper Alloy 0.8μm minimum	1						Country FR
	-Durability : 500 Matir -Delivered with Souriau contacts an							PN: 8	3D117W(
	-Temperature Range : -65°C to + -Salt Spray : 500 hours						A 23-09-201	6 First Release	
							ISS DATE Designed By:	Latest modification - by Date:	
							TITLE	A	luminium I
	BASIC SERIES: 8D 1 - 17 W 08 B N SHELL TYPE : In line Receptacle ORIENTATION : N ORIENTATION : N ORIENTATION : N SHELL SIZE : 17 SHELL SIZE : 17 CONTACT TYPE : SOCKET(500 Matings)					SCALE		neral linear olerances: ±	
						SOURIAU	WWW.SOL		
	PLATING : W = Olive drab Ca	admium		CONTAC	CONTACT LAY		FORMAT A3		
	H	G	F		E	1	D	C C	0117W08

σ					
			4		
S EXAMPLE			3		
any non-conformit which does not con r of the Parties or b dation, technical no ntry Jurisd R VWO8BN	mply with by a third party		2		
		MOD N°			
	CUSTOMER DRAWING				
um Inline plug 8D series					
r	NPRDS / PROJECT				
859					
.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission					
U DRG N° SHEET					
N08BN-C		1/2			
В	A				

_	Т	۵	ГТ	m	D	0	
		Contact Layout					
4	-x ($ \begin{array}{c} $					
	Cont positio A B C C D E F	Contacts (Insert arrangement 17-8) act X-axis (mm) Location Y-axis (mm) +.000 (0.00) +.236 (5.99) +.128 (3.25) +.086 (2.18) +.230 (5.54) 078 (1.98) +.094 (2.39) 216 (5.49) 030 (5.84) 078 (1.98)					
ယ	size no. co						
						SOURIAU shall not be lial due to a use of the Pro the Specifications issued by (professional reco	oducts w y either c
N						PN: 8D	Count FR
_					A 23-09-20 ISS DATE Designed By:	116 First Release	
					TITLE		miniur
					SCALE NA		ral linear rances: ±
					SOURIA	U WWW.SOUF	RIAU.C
					FORMAT A3		JRIAU 117W
L	Н	G	F	E	D	C	

			4		
			3		
any non-conformity or damage which does not comply with r of the Parties or by a third party dation, technical notice.)					
ntry Juris R 7W08BN	diction & Control List Not Listed		2		
	CUSTOMER DRAWING	MOD N°			
um Inline plug 8D series					
r	NPRDS / PROJECT 859				
.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission					
U DRG N° N08BN-C		SHEET 2/2			
В	A		-		

A

ω