



Datasheet for part number CIR06AF-32-22SX-F80-15

|   |
|---|
| Our Catalog Part Number: CIR06AF-32-22SX-F80-15   |
| Brand: VEAM Product Category: Circular Product Line: Veam CIR, VBN, Other Series: CIR / FRCIR |

|  |  |
|--|--|
| Product Datasheet  |  |
| SERIES   | Connector with Bayonet Coupling  |
| Shell Style  | Straight Plug Connector  |
| Environmental Class  | Backshell with A style clamp and bushing   |
| Shell Size   | 32   |
| Contact Arrangement  | 32-22  |
| Total Number of contacts                                   | 54 contacts  |
| Number of Contacts Size 16                                 | 54 contacts size 16  |
| Insulator Rotation   | 110°   |
| Gender   | Socket   |
| Contact Type   | Crimp for AWG wire (used in F80 insert)  |
| Contact Plating  | Silver   |
| Shell Material   | Aluminium alloy  |
| Shell Plating  | Olive drab chromate over cadmium plating (conductive)  |
| Wire Size Cross Section for Contacts with Modification -15 | 1,0 mm <sup>2</sup> or AWG18   |
| Shock Resistance   | Waterproof to 10 meters (33 ft)<br>12 h (14.7 PSI)   |
| Coupling   | 2000 couplings minimum   |
| Service Rating Letter                                      | A  |
| Operating Voltage DC                                       | 700 V  |
| Operating Voltage AC                                       | 500 V  |
| Dielectric strength - Minimum Flashover AC RMS             | 2800 V   |
| Dielectric strength - Test Voltage AC RMS (Hi Pot)         | 2000 V   |
| Note   | Voltages in excess of 30 V ac or 42.5 V dc are potentially hazardous and care should be taken to ensure that such voltages can't be transmitted in any way to exposed metal parts of the connector body. |
| General  | Veam CIR series Connectors are produced in accordance with NATO Standard VG95234, which is based on MIL-C-5015 for physical size, layout and environment requirements.                                   |