

Contact carriers - HC-M-EMV-ST/3-6 - 1678583

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



EMC contact carrier, 4-pos., shielded to connect shielded conductors from 3 - 6 mm conductor external diameter, male



Key commercial data

Packing unit	1 PCE
Weight per Piece (excluding packing)	40.9 GRM
Custom tariff number	85369010
Country of origin	Germany

Technical data

Electrical characteristics

Note	The EMC contact carriers are isolated from the housing potential. For CK 1,6...ED... crimp contacts (note in scope of delivery)
Rated voltage	42 V
Rated current	10 A
Number of positions	4

Mechanical characteristics

External cable diameter	3 mm ... 6 mm
-------------------------	---------------

General

Inflammability class according to UL 94	V0
Pollution degree	3
Surge voltage category	III

Material data

Contact material	Copper alloy
Contact carrier material	PC

Contact carriers - HC-M-EMV-ST/3-6 - 1678583

Classifications

eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	27143423
eCl@ss 5.1	27143423
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440209

ETIM

ETIM 3.0	EC000438
ETIM 4.0	EC000438
ETIM 5.0	EC000438

UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121522

Approvals

Approvals


Approvals

UL Recognized / GOST

Ex Approvals

Approvals submitted

Approval details

UL Recognized 

Contact carriers - HC-M-EMV-ST/3-6 - 1678583

Approvals



Accessories

Accessories

Assembly tool

Removal tool - HC-M-EMV-KON-EWZ - 1678635



Removal tool for HC-M-EMV contact carriers

Removal tool - VC-EW 1,6 - 1884869



Contact removal tool, for turned and rolled CK- 1.6-... contacts

Drawings

Contact carriers - HC-M-EMV-ST/3-6 - 1678583

Dimensioned drawing

