M12A-Coded Power Cables

N-Tron Networking Series



▶▶▶ IP67 Rated Power Cables



M12 IP67 Rated Power Cables


PRODUCT FEATURES

- IP67 rated power cable for use with N-Tron's M12 products
- M12 A code connector, bare wire
- -40°C to 85°C operating temperature
- · 18AWG 4 conductor cable
- Stranding: 7 x 26
- Insulation thickness: 0.010 in. (.254 mm)
- Jacket Thickness: 0.025" (0.64mm)
- Nominal O.D. 0.254" (6.45mm)

BUILT FOR EXTREME CONDITIONS

- · Water and sunlight resistant
- · Suitable for direct burial
- · Indoor / Outdoor use
- PLTC-ER, FPL, CMG, FT4
- PVC Insulation with Rip Cord





ORDERING INFORMATION

PART NUMBER

DESCRIPTION

PWR-M12-A-X PWR-RM12-A-X Power Cable, M12 A-Coded Straight Female to bare end, Shielded Power Cable, M12 A-Coded 90° Female to bare end, Shielded

Where:

X = length of cable, fill in desired amount in feet. Example: PWR-M12-A-X10 (for a 10 ft cable)



www.redlion.net

Connect. Monitor. Control.

Americas sales@redlion.net

Asia-Pacific asia@redlion.net

Europe Middle East Africa europe@redlion.net

+1 (717) 767-6511

As the global experts in communication, monitoring and control for industrial automation and networking, Red Lion has been delivering innovative solutions for over forty years. Our award-winning technology enables companies worldwide to gain real-time data visibility that drives productivity. Product brands include Red Lion, N-Tron and Sixnet. With headquarters in York, Pennsylvania, the company has offices across the Americas, Asia-Pacific and Europe. For more information, please visit www.redlion.net. Red Lion is a Spectris company.