	ت س	нт. 	m		0		A		
CHARCTERISTICS Solution Mile Classes Connector dimensional biolity 307 Mais 2014 Material : Baced on Mile Or 3899 Series (II : Shell Material : Baced on Mile Or 3899 Series (II : Shell Material : Baced on Mile Or 3899 Series (II : Shell Material : Baced on Mile Or 3899 Series (II : Shell Material : Baced on Mile Or 3899 Series (II : Shell Material : Baced on Mile Or 3899 Series (II : Shell Material : Baced on Mile Or 3899 Series (II : Shell Material : Baced on Mile Or 3899 Series (II : Shell Material : Stormatic or 399 with in Dimensional : Shell Material : Stormatic or 399 with in Dimensional : Shell Material : Stormatic or 399 with in Dimensional : Shell Material : Stormatic or 399 with in Dimensional : Shell Material : Stormatic or 399 with in Dimensional : Shell Material : Stormatic or 399 with in Dimensional : Shell Material : Stormatic or 399 with in Dimensional : Shell Stormatic Ordination : Shell Material : Stormatic ordination : Shell		ØS						4	
CPACTERST Sundard is lead on ML IDT 38990 Series III Shell Naterial X Shell N					LAYOUT SHOWN AS EXA	AMPLE		3	
CHARCTERISTICS -Standard: Based on MIL-DT-38999 Series III -Seli Material: :Auminium -Seli Material: :Auminium -Seli Material: :Auminium -Seli Material: :Belex Zin: Nickel -soulator: :Dim :Dim -Contacts Billow Time: Nickel -soulator: :Contact Palang: :SOUBLAU shall not be liable for any non-conformity or damage due to a use of the Products which dees not comply with due to a use of the Products which dees not comply with due to a use of the Products which dees not comply with due to a use of the Products which dees not comply with due to a use of the Products which dees not comply with due to a use of the Products which dees not comply with due to a use of the Products which dees not comply with due to a use of the Products which dees not comply with due to a use of the Products which dees not comply with due to a use of the Products which dees not comply with due to a use of the Products which dees not comply with the Specifications issued by either of the Parties or by a billing Dase (protect whith Source context and Accessories -Temperature Range::::::::::::::::::::::::::::::::::::		Keving Shown as example							
-Standard: Based on MIL-0TL-38999 Series III -Shell Material: ::::::::::::::::::::::::::::::::::::	CHARACTERISTICS		ator dimension						
Shell Mattelli 2 31 Max U 31 Max U 31 Max SURIAU shall not be liable for any non-conformity or damage U Height for the set of		Dim	Nominal						
Seals & Grommet :: Silicon Elastormer Contact Plating :: Gold over copper Alloy 0.8µm minimum 2 -Ourability :: Sto Mating cycles -Durability :: Sto Mating cycles PN: 8D517Z06AN 2 -Uurability :: Sto Mating cycles -Delevered with Souriau contacts and Accessories -	-Shell Plating: Black Zinc Nickel-Insulator: Thermoplastic	Z	31 Max	due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party					
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range : 65°C to +175°C -salt Spray : 500 hours -Mass : 29.9 g ± 10% BASIC SERIES: 8D 8D -17 Z 06 Mass -17 SHELL SIZE : 17 -17 <	-Seals & Grommet : Silicon Elastomer	m							
-Salt Spray ± 500 hours -Mass ± 29.9 g ± 10% BASIC SERIES: 8D 5 - 17 Z 06 A N BASIC SERIES: 8D 5 - 17 Z 06 A N SCALE General linear NPRDS / PROJECT SHELL TYPE : Standard Crimp Contact 0 0 N SCALE General linear NPRDS / PROJECT SOURIAU SOURIAU SOURIAU SOURIAU SOURIAU SOURIAU SOURIAU SOURIAU It must not be reproduced or communicated without permission PLATING : Z Black Zinc Nickel CONTACT TYPE : PIN(500 Matings) CONTACT LAYOUT : 17-06 A A A A BD517Z06AN-C 1/2	-Durability : 500 Mating cycles								
-Mass : 29.9 g ± 10% -Mass : 29.9 g ± 10% 				A 18-10-2016	First Release			_	
BASIC SERIES: 8D 5 - 17 Z 06 A N SCALE Tolerances: t 859 5 5 5 5 5 5 5 5 5 5 6 A N A A A Basic Series: Tolerances: t 859 5 5 5 5 5 6 A N A A Basic Series: Tolerances: t 6 <t< td=""><td></td><td></td><td></td><td></td><td></td><td>CUSTOME</td><td></td><td>,</td></t<>						CUSTOME		,	
BASIC SERIES. ab 3 17 2 00 A N Tolerances: 17 17 2 00 A N Tolerances: 17 17 17 2 00 A N NA Tolerances: 17 17 2 00 A N NA Tolerances: 17 1		TITLE Aluminium Plug 8D series							
CONTACT TYPE : Standard Crimp Contact ORIENTATION : N SOURIAU SOURIAU.COM SOURIAU SHELL SIZE : 17 CONTACT TYPE : PIN(500 Matings) CONTACT LAYOUT : 17-06 FORMAT SOURIAU DRG N° SHEET PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 17-06 FORMAT SOURIAU DRG N° SHEET 1/2 Image: Standard Crimp Contact Image: Standard Crimp Contact Image: Standard Crimp Contact SOURIAU		Z 06 A N		-	Tolerances:	8	359	-	
PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 17-06 FORMAT SOURIAU DRG N° SHEET A3 8D517Z06AN-C 1/2							SOURIAU st not be reproduced or		
55517200/WC		PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 17-06				SHEET			
	Н	F	F						

	τ		G	г г	m		0	
		Contact Lay	out					
4		-× -× +Y A +Y A + + + + + + + + + + + + +	B → ×					
		Contacts (Insert arrangement 1 Contact Local	7-6)					
З		position ID X-axis (mm) A +.121 (3.07) B +.241 (6.12) C +.000 (0.00) D 241 (6.12) E 121 (3.07)	Y-axis (mm) +209 (5.31) -241 (6.12) +000 (0.00) +209 (5.31) +000 (0.00)					
	Shell Arranger size no. 17 -6		Service Contact Supersedes rating location I All MS20053-6					
							due to a u the Specificatio	all not be liable for ar use of the Products w ons issued by either c essional recommenda
N								Count FR PN: 8D5172
						A 1 ISS Designed	.8-10-2016 First Release DATE Latest modifica	ation - by
						SCALE		Alumir General linear Tolerances:
4						SOU		± W.SOURIAU.(
				1	,	FORMAT A3		SOURIAU 8D517Z
	Н		G	F	E	D	C	

