

## Datasheet for part number CA01COME20-19PB

|   | Our Catalog Part Number: CA01COM-E20-19P-B   |  |  |
|---|--|--|--|
| Our Global Manufacturing Part Number: 121647-2076 |  |  |  |
| Ī   | Brand: Cannon Product Category: Circular Product Line: CA Bayonet Series: CA COM-B |  |  |

| Product Datasheet                                   |  |
|---|--|
| Bayonet   | Connector with Bayonet Coupling  |
| Shell Style   | Cable connecting plug  |
| Endbell Style                                       | Endbell with clamp and bushing (w/o grommet and ferrule)   |
| Gender  | Pin  |
| Shell Size  | 20   |
| Contact Arrangement                                 | 20-19  |
| Number of contacts                                  | 3 contacts size 8  |
| Contact Type  | Solder Cup   |
| Contact Plating                                     | Hard silver  |
| Contacts installed                                  | yes  |
| Contact Rating at +20 °C (68 °F)<br>(Size 60/100/8) | 74 A   |
| Contact Resistance (Size 60/100/8)                  | 1 mΩ   |
| Operating Voltage                                   | In case of voltages greater than 50V the connector<br>must be used in accordance with DIN VDE part 410,<br>IEC 60364-4-41.                     |
| Insulator Resistance                                | ≥1000 MΩ   |
| Test Voltage  | 1600 Vrms  |
| Air and Creepage Paths (Min)                        | 1,1 mm   |
| Ambient Temperature                                 | Standard insulator material -55°/+125°C<br>(-67/257°F)   |
| Safety Provisions                                   | IP67 (only applies if a grommet is used)   |
| Mating Cycles                                       | 500 min  |
| Sep. Force per Contact (Size 60/100/8)              | 3,0 N  |
| Gauge   | For infos on Gauge please see catalog<br>VG95234, part 1   |
| Coupling Torque                                     | Closing: 4,5 Nm max / Opening: 0,7 Nm min  |
| Contact Retention (Size 60/100/8)                   | 80 N   |
| Shell Material                                      | Aluminium alloy  |
| Shell Plating                                       | Nickel plated  |
| Insulator and Gromet Material                       | CR-Elastomere  |
| Contact Material                                    | Copper alloy   |
| Harnessing Info: Contact Cross-Section              | See assembly instruction   |
| Harnessing Info: Insulator Diameter                 | See assembly instruction   |
| Wire Stripping (Size 60/100/8)                      | 11,8 mm  |
| General Info  | All tests in accordance with VG95319 and/or if<br>applicable with VG95210 except salt spray resistance<br>and heat and humidity endurance test |