ב בר	т (п	D	0	B		
			LAYOUT SHOWN AS EXAMI	PLE		
	Keying Shown as example					
CHARACTERISTICS	Connector dimension					
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium	DimNominalØS29.4 Max					
-Shell Plating : Nickel	Z 31 Max VV THREAD M18x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with			
-Insulator : Thermoplastic			the Specifications issued by either of the Parties or by a third party			
-Contacts : Copper Alloy			(professional recommendation, technical notice.)			
-Seals & Grommet : Silicon Elastomer			Country	Jurisdiction & Control List		
-Contact Plating : Gold over copper Alloy 0.8μm minimum			FR	Not Listed		
-Durability : 500 Mating cycles			PN: 8D513F26SB			
-Delivered with Souriau contacts and Accessories			FIN. 6U313F20	סכו		
-Temperature Range : -65°C to +200°C		A 17-10-2016	First Release			
-Salt Spray : 48 hours						
Mass : 27.44 g ± 10%		ISS DATE Designed By:	Latest modification - by Date:		10D N°	
		TITLE				
BASIC SERIES: 8D 5 - 13 F	26 S B	SCALE	General linear Tolerances:	NPRDS / PROJECT		
SHELL TYPE : Plug with RFI Shielding		NA		859	. (
CONTACT TYPE : Standard Crimp Contact	ORIENTAT		OURIAU This document is the property of SOURIAU it must not be reproduced or communicated without permission			
SHELL SIZE : 13	CONTACT TYPE : SOCKET(500 N					
PLATING : F = Nickel	CONTACT LAYOUT		SOURIAU DE		SHEET	
	CONTACT LATOUT		JOUNIAU DI			
		A3	8D513F265	SB-C	1/2	

_	Ŧ	۵	г П	m	D	0
		Contact Layout				
4		26				
		2#12 6#22D				
ω	Ctc A B C D E F 1 2	13-26 X Y 0 3.47 2.47 4.34 2.47 -4.34 0 -3.47 -2.47 -4.34 -2.47 -4.34 3.25 0 -3.25 0				
	_					SOURIAU shall not be liable for an
N						due to a use of the Products w the Specifications issued by either o (professional recommenda Count FR PN: 8D513
_					A 17-10-201 ISS DATE Designed By:	16 First Release Latest modification - by Date:
					TITLE	Alumir
→					SCALE NA	General linear Tolerances:
					SOURIAL	J WWW.SOURIAU.C
					FORMAT A3	SOURIAU
	Н	G	F	E		8D513F
			•	-	V	- ·

