

This document is the property of Amphenol Corporation and is delivered on the express condition that it is not to be disclosed, reproduced or used, in whole or in part, for manufacture or sale by anyone other than Amphenol Corporation without its prior consent, & that no right is granted to disclose or to use any information in this document.

REVISIONS				
SYM	ECN	DESCRIPTION	DATE	APPROVED
A			07/06/07	

**D-SUB TECHNICAL DATA**

Material and finish: plastic, nickel plated

Cable strain relief: Steel fibre reinforced Polycarbonate (UL94R-0) for ENI/RFI screening

Locking screws: Long solid jackscrew with full metal for indication of M3 thread

Temperatruue range: -55°C to 125°C

Cable diameter: 4.0 to 13.0mm


Attenuation factor: >40 dB between 30 MHz and 1 GHz

Meet requirements: VDE 0971, FCC 20780, 89/336/EU

MARKING : Amphenol-...(Series No.)

Commercial reference

Manufacturing date



UNLESS OTHERWISE SPECIFIED TOLERANCES U.S. METRIC .X +/- 0.50 .XX +/- 0.30 .XXX +/- 0.20 FRACTIONS +/- ANGLES +/- 2°	APPROVAL	DATE
	DRAWN Lisa.peng	07/06/07
	CHECKED Mh.wang	07/06/07
FOR MATERIALS AND FINISHES SEE NOTES	DRAWING FILE : PE master/drawing/Dsub	
REMOVE SHARP EDGES	ANGLE OF PROJECTION	
DIMENSIONS		
U.S. INCHES		
METRIC MM		

Amphenol	
TITLE <b>PLASTIC HOOD</b>	
SIZE	DRAWING NO.
A4	L17DPPK15MJS
SCALE	NONE
SHEET 1 OF 1	

A

A