ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב ב	m rr		0	B	
>			LAYOUT SHOWN AS EXAN	1PLE	
	Keying Shown as example				
CHARACTERISTICS	Connector dimension				
-Standard : Based on MIL-DTL-38999 Series III	DimNominalØS35.7 Max				
-Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy	Z31 MaxVV THREADM25x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)		
-Seals & Grommet : Silicon Elastomer			Country Jurisdiction & Control List FR Not Listed		
-Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles					
-Delivered with Souriau contacts and Accessories			PN: 8D517W0	1030	
-Temperature Range : -65°C to +175°C		A 17-10-2016	First Release		
-Salt Spray : 500 hours		ISS DATE	Latest modification - by		MOD N°
Mass : 39.5 g ± 10%		Designed By:	Date:	CUSTOMER DRAWING	
		TITLE	ITLE Aluminium Plug 8D series		
BASIC SERIES: 8D 5 - 17 W	06 S C	SCALE	General linear	NPRDS / PROJECT	
SHELL TYPE : Plug with RFI Shielding		NA .	Tolerances:	859	
CONTACT TYPE : Standard Crimp Contact	ORIEN			This document is the propert	ty of
SHELL SIZE : 17	CONTACT TYPE : SOCKET(50	SOURIAU	SOURIAU WWW.SOURIAU.COM SOURIAU it must not be reproduced or communicated without permission		
PLATING : W = Olive drab Cadmium	CONTACT TIPE : SOCKET(SO		SOURIAU D		SHEET
	CONTACT LAFC	/01.1/-00			
<u>_</u>		A3	8D517W06		1/2

r	工	G	г –	m	Ū	0
		Contact Layout				
4		Em Ap				
	-x ($ \stackrel{E}{\to} \stackrel{A}{\to} \\ \stackrel{D}{\oplus} \stackrel{E}{\to} \stackrel{B}{\to} \stackrel{B}{\to} \cdot \times $				
	Conta position A	(mm) (mm) +.121 (3.07) +.209 (5.31)				
යා	B C D E F	+.000 (0.00)241 (6.12) 241 (6.12) +.000 (0.00) 121 (3.07) +.209 (5.31)				
	size no. co	mber of ntacts Size contacts Service rating Contact location Supersedes 6 12 I All Mts20053-6				
						SOURIAU shall not be liable for ar due to a use of the Products w the Specifications issued by either o (professional recommenda
N						Count FR
						PN: 8D517
						016 First Release
					ISS DATE Designed By:	Date:
					SCALE	Alumir General linear
→					NA	Tolerances:
					SOURIA	
		1			FORMAT A3	SOURIAU 8D517W
	Н	G	l F	E \	D	C

Φ		A	•		
					4
					3
any non-conformit which does not co r of the Parties or b dation, technical n ntry Jurisc R 7W06SC	mply with by a third otice.)	h party Control List			2
inium Dlug 9		DMER DRAWING	N	/IOD N°	
inium Plug 8	NPR	RDS / PROJECT 859			1
.COM U DRG N° W06SC-C	i	is document is the p SOURIAU t must not be reproc nmunicated without	luced o	r	
В		A			I