

| | ω | | | A | | | | |
|--|---|------|----------|-------|--------------|---|--|--|
| | 6 | | | | | 4 | | |
| | | | | | | | | |
| | AMPLE | | | | | 3 | | |
| any non-conformity or damage which does not comply with er of the Parties or by a third party adation, technical notice.) | | | | | | | | |
| Intry R 1S | Jurisdiction & Control List Not Listed | | | | | | | |
| | | CUST | OMER DR/ | AWING | MOD N° | | | |
| ess Steel Plug 8D series | | | | | | | | |
| ar : | NPRDS / PROJECT 859 | | | | | | | |
| This document is the property of SOURIAU it must not be reproduced or communicated without permission | | | | | | | | |
| | DRG N° 4AN-C | | | | SHEET 1/2 | | | |
| | В | | | А | | L | | |
| | | | | | | | | |

| ſ | Ξ | G | г т | m | D | 0 |
|---------|--|---|------------|---|--------------|---|
| | | Contact Layout | | | | |
| 4 | y. | $ \begin{array}{c} $ | | | | |
| | Conta positi ID A B C D Shell Arrangement size no. conta conta | X-axis Y-axis (mm) +0.65 (1.65) +0.65 (1.65) +0.65 (1.65) -0.65 (1.65) -0.65 (1.65) -0.65 (1.65) -0.65 (1.65) +0.65 (1.65) -0.65 (1.65) +0.65 (1.65) -0.65 (1.65) +0.65 (1.65) -0.65 (1.65) +0.65 (1.65) -0.65 (1.65) +0.65 (1.65) | | | | |
| ى | | | | | | |
| | L | | | | | |
| | | | | | | SOURIAU shall not be liable for an due to a use of the Products w the Specifications issued by either o (professional recommenda |
| N | | | | | | PN: 8D511 |
| | | | | | ISS DATE | 16 First Release Latest modification - by |
| | | | | | Designed By: | Date: Stainles |
| | | | | | SCALE NA | General linear Tolerances: |
| | | | | | FORMAT | |
| | | | 1 | | A3 | SOURIAL 8D511S |
| | Н | G | F | E | D | C |

