

## Specification Sheet

Part Number: T150R0X2



Heavy Duty Cable Tie, 15.4" Long, UL Rated, 175lb Tensile Strength, PA66, Black, 25/pkg

<b>Article Number</b>	111-15200
<b>Type</b>	T150R(U)
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Heavy duty design to offer higher tensile strength.</li><li>• Head design provides high tensile strength with very low insertion force.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
<b>Short Description</b>	Heavy Duty Cable Tie, 15.4" Long, UL Rated, 175lb Tensile Strength, PA66, Black, 25/pkg

Global Part Name

T150R(U)-PA66-BK

Minimum Tensile Strength (Imperial)

175.0

Minimum Tensile Strength (Metric)

780.0

Length L (Imperial)

15.4

Length L (Metric)

390.0

Identification Plate Position

none

Releasable Closure

No

Variant

Inside Serrated

Width W (Imperial)

0.35

Width W (Metric)

8.9

Bundle Diameter Min (Imperial)

0.32

Bundle Diameter Min (Metric)

8.0

Bundle Diameter Max (Imperial)

4.1

Bundle Diameter Max (Metric)

104.1

Material

Polyamide 6.6 (PA66)

<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	UL-ZODZ2.E64139
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity(Imperial)</b>	25
<b>Package Quantity (Metric)</b>	25
<b>Customs Number</b>	3926909987
<b>Content Unit(BMEcat)</b>	pcs.