



Click [here](#) for the 3D model.

| Dimensions | |
|------------|-----------------|
| L | 30.5mm -0.5mm |
| H | 17.3mm -0.5mm |
| T | 10.6mm -0.5mm |
| S | 25.4mm +/-0.4mm |
| LL | 6mm -1mm |
| F | 1mm +/-0.05mm |

| Packaging Specifications | |
|--------------------------|------|
| Packaging | Tray |
| Packaging Quantity | 1000 |

| General Information | |
|---------------------|--|
| Series | PME261/P561 |
| Dielectric | Metallized Paper |
| Style | Radial |
| Features | Pulse in DC and low frequency applications |
| RoHS | Yes |
| Lead | Wire Leads |
| AEC-Q200 | No |
| Construction | Molded |
| Miscellaneous | AC Operation: 70C MAX. |

| Specifications | |
|-----------------------|-------------|
| Capacitance | 0.47 uF |
| Capacitance Tolerance | 10% |
| Voltage AC | 220 VAC |
| Voltage DC | 400 VDC |
| Temperature Range | -40/+100°C |
| Rated Temperature | 85°C |
| Dissipation Factor | 1.3% 1kHz |
| Insulation Resistance | 8.511 GOhms |
| Max dV/dt | 370 V/us |