	ד G T	n m	D	0	Β	A		_
4 3	R 22.6 Max () () () () () () () () () () () () () (WN AS EXAMPLE			4
	Ke CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	eying Shown as example Connector dimension Dim Nominal						
N	-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8μm minimum-Durability: 500 Mating cycles	A 34.9±0.3 B 19.07+0.1/-0.15 R 32.5Max S 31.8±0.4 W 2.2+0.9/-0.1 VV THREAD M15x1-6g		the Specifications issued by (professional recom	ducts which does not compleither of the Parties or by a mendation, technical notic Country Jurisdiction FR N	y with third party		2
	-Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +175°C -Salt Spray : 500 hours			2016 First Release	711W02BA			
	-Mass : 20.34 g ± 10%		ISS DAT Designed By:	Date:		USTOMER DRAWING	MOD N°	
			TITLE Aluminium Receptacle 8D series				-	
<u> </u>	BASIC SERIES: 8D 7 - 11 W 02 SHELL TYPE : Jam nut Receptacle	B A	SCALE NA	General Tolera ±-	nces:	NPRDS / PROJECT 859		1
	CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11	ORIENTATION : A CONTACT TYPE : SOCKET(500 Matings)	SOURIA	WWW.SOURI	AU.COM	This document is the prope SOURIAU it must not be reproduced communicated without perr	d or	
	PLATING : W = Olive drab Cadmium	CONTACT LAYOUT : 11-02	format A3		RIAU DRG N° 11W02BA-C		SHEET 1/2	
L	H G F	E E	D	С	В	А		

Г	ت	т (Г		▶ 8		
4	Contact Layout		Panel cutout JAM NUT RECEPTACLE (TYP	E 7)		4
	Contacts Contact arrangement 11-2) Contact position Contact location position X-axis Y-axis ID (mm) (mm) A +.095 (2.41) +.000 (.00) B 095 (2.41) +.000 (.00) Shell Arrangement Number of contacts Stevice contact size no. contacts contacts rating 11 -2 2 16 I All			lominal 59+0/-0.25		_
3			ØC 20.9	96+0.25/-0		3
2			due to a use of the Specifications is:	t be liable for any non-conformity or damage the Products which does not comply with sued by either of the Parties or by a third party al recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed		2
			A 01-10-2016 First Release	PN: 8D711W02BA		_
_			ISSDATELatest modificationDesigned By:Date:	- by CUSTOMER DRAWING	MOD N°	-
			TITLE	TITLE Aluminium Receptacle 8D series		
_				VA Tolerances: ± NA Tolerances: ± This document is the pro- SOURIAU		1
				communicated without permission		
				8D711W02BA-C	2/2	
_	H G	F	DC	BA		