

## Specification Sheet

Part Number: RT150REP0X2



Releasable Cable Tie, Release Tab, 15.4" Long, 175lb Tensile Strength, PA66, Black, 25/pkg

Article Number	115-00036
Type	RT150REP
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>• Special design with extended pawl offers a release feature for quick and easy access to wire bundles.</li><li>• Head design provides high tensile strength with very low insertion force even after repeated use.</li></ul>
Quantity Per	bag

### Product Description

HellermannTyton Releasable Cable Ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

<b>Short Description</b>	Releasable Cable Tie, Release Tab, 15.4" Long, 175lb Tensile Strength, PA66, Black, 25/pkg
<b>Global Part Name</b>	RT150REP-PA66-BK
<b>Minimum Tensile Strength (Imperial)</b>	175.0
<b>Minimum Tensile Strength (Metric)</b>	780.0
<b>Length L (Imperial)</b>	15.4
<b>Length L (Metric)</b>	390.0
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	Yes
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.35
<b>Width W (Metric)</b>	8.8
<b>Bundle Diameter Min (Imperial)</b>	0.32
<b>Bundle Diameter Min (Metric)</b>	8.0
<b>Bundle Diameter Max (Imperial)</b>	4.1
<b>Bundle Diameter Max (Metric)</b>	105.0

<b>Cable Tie Width Max (Imperial)</b>	0.35
<b>Cable Tie Width Max (Metric)</b>	8.8
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL 94 V2
<b>Operating Temperature (Metric)</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	25
<b>Package Quantity (Metric)</b>	25
<b>Customs Number</b>	3926909987