

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C
	OPERATING&STORAGE HUMIDTY RANGE	85%MAX	APPLICABLE CABLE	CABLE DIAMETER : ϕ 5.8~6.8
	VOLTAGE		CURRENT	

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION

GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
--	-------	--------------------------	----------	---------	------

REMARK THIS PRODUCT SHALL BE MATED WITH DH3*17S,IT APPLIES TO DH3*B-17S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS. Unless otherwise specified, refer to JIS C 5402.	APPROVED	KN. ICHIKAWA	10.07.05
	CHECKED	KN. ICHIKAWA	10.07.05
	DESIGNED	TU. TANIGUCHI	10.07.05
	DRAWN	TU. TANIGUCHI	10.07.05

Note QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC4-126590-00
--	-------------	----------------

HRS	SPECIFICATION SHEET	PART NO.	DH-17-CV2B	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL244-0013-3-00	1/1