




## Han-Fast Lock 4-6mm<sup>2</sup>, Ag



Part number	09 08 000 7923
Specification	Han-Fast Lock 4-6mm <sup>2</sup> , Ag
HARTING eCatalogue	<a href="https://b2b.harting.com/09080007923">https://b2b.harting.com/09080007923</a>

### Identification

Category	Contacts
Series	Han-Fast <sup>®</sup> Lock
Type of contact	PCB contact
Description of the contact	Without pin

### Version

Pack contents	Single contact
---------------	----------------

### Technical characteristics

Conductor cross-section	4 ... 6 mm <sup>2</sup>
Operating current	≤60 A
Contact resistance	≤2 mΩ
Stripping length	7.5 mm

### Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material (locking)	Copper alloy
Surface (locking)	Passivated
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No



Pushing Performance

## Material properties

REACH SVHC substances	No
California Proposition 65 substances	Yes

## Specifications and approvals

UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
----------	--

## Commercial data

Packaging size	100
Net weight	1.22 g
Country of origin	Germany
European customs tariff number	85366990
eCl@ss	27460201 PCB connector (board connector)