Product data sheet Characteristics

ZCMD21M12

Limit switch body, Limit switches XC Standard, ZCMD, 1C/O, silver, snap action, connection, M12





Main

Series name Standard format Product or Component Type Device short name ZCMD Design Miniature Body type Fixed Associated head ZCE29	Range of product	Telemecanique Limit switches XC Standard
Device short name ZCMD	Series name	Standard format
Design Miniature		Limit switch body
Body type	Device short name	ZCMD
Associated head ZCE29 ZCE06 ZCE62 ZCE09 ZCE13 ZCE67 ZCE10 ZCE14 ZCE07 ZCE08 ZCE65 ZCE65 ZCE61 ZCE64 ZCE7 ZCE10 ZCE24 ZCE11 ZCE27 ZCE64 ZCE27 ZCE66 ZCE28 ZCE66 ZCE28 ZCE66 ZCE21 Body Material Zamak Number of poles 2 Contacts type and composition	Design	Miniature
ZCE02	Body type	Fixed
Number of poles 2 Contacts type and composition 1 C/O	Associated head	ZCE02 ZCE06 ZCE62 ZCE09 ZCE13 ZCE67 ZCE10 ZCE14 ZCE07 ZCE08 ZCE65 ZCEG1 ZCEF0 ZCE52 ZCE7 ZCE24 ZCE11 ZCE27 ZCE64 ZCE72 ZCE66 ZCE66 ZCE01 ZCE66
Contacts type and 1 C/O composition	Body Material	Zamak
composition	Number of poles	2
Contact operation Span action		1 C/O
Outlant operation Shap action	Contact operation	Snap action

Complementary	
Product Compatibility	XCMD
Electrical connection	Male connector M12, 4 pins
Contacts insulation form	Za
Contacts material	Silver plated contacts
Positive opening	Without
Minimum actuation speed	0.01 m/min
[le] rated operational current	0.1 A 250 V, DC-13 EN/IEC 60947-5-1 appendix A 1.5 A 240 V, AC-15 EN/IEC 60947-5-1 appendix A
[Ithe] conventional enclosed thermal current	3 A
[Ui] rated insulation voltage	300 V 3)UL 508 300 V 3)CSA C22.2 No 14 250 V 3)IEC 60947-5-1
Maximum resistance across terminals	25 mOhm IEC 60255-7 category 3
[Uimp] rated impulse withstand voltage	2.5 KV IEC 60664

2.5 kV IEC 60947-1

Electrical durability	5000000 Cycles, DC-13 24 V, 3 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 Cycles, DC-13 48 V, 2 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 5000000 cycles, DC-13 120 V, 1 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C
Width	1.18 in (30 mm)
Height	1.97 in (50 mm)
Depth	0.63 in (16 mm)
Product Weight	0.14 lb(US) (0.065 kg)
Environment	
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Ordering and shipping details	
Category	22413 - LIMIT SWITCH, IEC, MINIATURE
Discount Schedule	
GTIN	3389110299144
Nbr. of units in pkg.	1
Package weight(Lbs)	2.68 oz (76 g)
Returnability	Yes
Country of origin	ID
Package 1 Height Package 1 width Package 1 Length	0.67 in (1.7 cm) 2.09 in (5.3 cm) 2.09 in (5.3 cm)
Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☐REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) ELU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
Contractual warranty	

18 months

Warranty