


NOTE:  
 1.MATERIAL: C2300 BRASS T-0.35mm,TIN PLATED  
 2.EVERY REEL QUANTITY: 2000± 10PCS (ROLL BAND)

UNLESS OTHERWISE SPECIFIED  
 DIMENSIONS ARE IN mm  
 TOLERANCE  
 DECIMALS ANGULAR  
 X±0.25 ±1°  
 XX±0.13  
 DO NOT SCALE DRAWING



METRIC  
 COMPONENT

LITTELFUSE PART NO.	REELED	REVERSE REEL	WIRE GAGE	INTERLEAF	GRIP TYPE			
					A	B	C	D
913-007	YES	NO	10	YES	5.08	5.08	7.11	6.10
913-007-R	YES	YES	10	YES	5.08	5.08	7.11	6.10
913-007-001	NO	NO	10	NO	5.08	5.08	7.11	6.10
913-008	YES	NO	14	YES	4.06	4.06	5.33	4.83
913-008-R	YES	YES	14	YES	4.06	4.06	5.33	4.83
913-008-001	NO	NO	14	NO	4.06	4.06	5.33	4.83

NO	COMPONENT NO	DESCRIPTION	QTY/M	U/M
BILL OF MATERIAL				
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN BRACKETS [ ] ARE INCHES				
UNLESS OTHERWISE SPECIFIED, DIMENSIONS DO NOT INCLUDE PLATING.				
⊙	DENOTES CRITICAL CHARACTERISTICS.			
CPK	DENOTES CPK DIMENSIONS, -MINIMUM CPK VALUE			
ST	DENOTES A CHARACTERISTIC THAT PROVIDES AN INDICATION OF PROCESS PERFORMANCE. PROCEDURE FOR MEASUREMENT AND TRACKING TO BE DEFINED IN LITTELFUSE INSPECTION INSTRUCTIONS			
CP	DENOTES CP DIMENSIONS, -MINIMUM CP VALUE MUST BE WITHIN THE DIMENSIONAL LIMITATIONS SHOWN ON DRAWING AND INITIALLY LOCATED TO ALLOW FOR MAXIMUM TOOL LIFE			

COPIES TO		MATERIAL SPEC		SEE NOTE	
1	9	FINISH	SEE NOTE	SCALE	2:1
2	10	DRW E JIN	DATE 12/12/11	SUPER DR	
3	12	CHK	DATE	FINISH GOOD WT	
4	13	APPD	DATE	GRAMS/PIECE	
5	14	TOLERANCES UNLESS OTHERWISE SPECIFIED (REF. ISO 2768-FH)			
6	15	UP TO 0.5	UP TO 3	UP TO 6	UP TO 30
7	16	OVER 0.5	OVER 3	OVER 6	OVER 30
8	17	TOLERANCE	3 - 6	6 - 120	120 - 400
3RD ANGLE PROJECTION					
TITLE					
CRIMP TERMINAL WITH INSULATION GRIP					
REVISION DRWG. NO. OL-913-007					
OUTLINE					

LTR	DATE	REVISION	CHK	APD
A	12/12/11	503915ERA-NEW RELEASED E JIN		
B	08/17/12	505864ECA-SEE ECO FYUE		
C	10/26/12	506401ERA-RELEASE 913-007-001 AND 913-008-001 FYUE		
D	01/22/14	509992ERA-RELEASE 913-007-R AND 913-008-R FYUE		

