



Configuration:  
HD15M

		BNC PLUG
1	Red	1 (Cen.)
6	Red(GND)	1 (Shield)
2	Green	2 (Cen.)
7	Green(GND)	2 (Shield)
3	Blue	3 (Cen.)
8	Blue(GND)	3 (Shield)
13	White	4(Cen)
11	GND(White+Black)	4,5(Shield)
14	Black	5(CEN)

**Material:**

- 1.Cable:#28,UL2919,75 Ohm, 5COAX+Spiral,O.D.8.5
- 2.Connector: HD15M, 9th Empty, Black  
BNC Plug
- 3.Thumbscrew:#4-40UNC, E32
- 4.Black Heat Shrink Tube(HD15M USE):  
  - ∅ 1.5X15:4PCS
  - ∅ 3X8:3PCS
  - ∅ 5.0X8:1PC

**Note:**

- 1.Total Length: 2000±50mm
- 2.Color:Black
- 3.Molded Type



ITEM NO	<b>AK553-2-R (2.0 M)</b>
TITLE	<b>CABLE VGA TO 5 X BNC MONITOR</b>

**ASSMANN**  
Electronics, Inc.

1840 W. Drake Drive, Suite 101 - Tempe, AZ 85283  
Toll Free: 1-877-277-6266 Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED  
© Copyright 2008 by Assmann Electronic Components  
All International Rights Reserved