	۳ ۳	m		0	Ξ			
Image: State in the state	4						4	
CHARACTERSTICS Sundard: Based on MIL DTL 38999 Series III. Shell Material :: dluminium Shell Material :: dluminium dluminium Shell Shell :: dluminium dluminium Shell :: dluminium d				LAYOUT SHOWN AS EX	XAMPLE		ę	
Standard : Based on MIL-DT-38999 Series III Difficution with the series of the Products with does not comply with the series of the product with does not comply with the series of the product with does not comply with the series of the product withered withered with product with does not comply with doe	Keying Sł	own as example						
Shell Material : Aluminium -Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contact : Cooper Alloy Qium minimum -Seals & Grommet : Slick Din Elastomer -Contact Plating : Gold over copper Alloy Qium minimum -Seals & Grommet : Slick On Mating cycles -Oelevered with Souriau contacts and Accessories - -Temperature Range : - 657 Cto +1757 C -Sail Spray : 500 hours -Mass : 40.08 g ± 10% Basic SERIES: 8D 5 - 17 Z 99 N ORIENTATION: N Contract TryPE : Sloadard Crimp Contact NORD Previous NORD Previous Shell LTYPE : Plug with RFI Shielding - 17 Z 99 N Contract TryPE : Sloadard Crimp Contact NORD Previous Shell LTYPE : Flug with RFI Shielding - 17 Z 99 N Contract TryPE : Sloadard Crimp Contact NORD / PROJECT Shell LTYPE : Flug with RFI Shielding - 17 Z 99 N N Sourclause NORD Previouse Sourclau O								
 -Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +175°C. -Sait Spray : 500 hours. -Mass : 40.08 g ± 10% Mass : 40.08 g ± 10% A 18-10-2016 First Release ISS DATE Latest modification - by MoD N^a Designed By: Designed By: D	-Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer	ØS 35.7 Max Z 31 Max VV THREAD M25x1-6g SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)						
- Salt Spray :: 500 hours -Mass :: 40.08 g ± 10% -Mass :: 40.08 g ± 10% -Ma			PN: 8D517Z99SN					
-Mass : 40.08 g ± 10% - Mass : 40.08 g ± 10% - Mass : 40.08 g ± 10% - Mass : 40.08 g ± 10% - Mon v - Mon v - Mon v - Mon v - Designed By: Date: Customer Drawing - Designed By: Date: Customer Drawing - Mon v - Designed By: Date: Customer Drawing - Designed By: Date: Customer Drawing - Designed By: Date: Customer Drawing - Mon v - Designed By: Date: Customer Drawing - Designed By: Date: Desi			A 18-10-2016	First Release				
BASIC SERIES: 8D 5 - 17 Z 99 S N CONTACT TYPE Standard Crimp Contact ORIENTATION : N SCALE General linear NPRDS / PROJECT SHELL SIZE : 17 CONTACT TYPE : Standard Crimp Contact ORIENTATION : N SOURIAU WWW.SOURIAU.COM This document is the property of SOURIAU PLATING : Z = Black Zinc Nickel CONTACT TYPE : SOCKET(500 Matings) FORMAT SOURIAU DRG N° SHEET							<u>N°</u>	
BASIC SERIES: 8D 5 - 17 Z 99 S N SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact 0RIENTATION : N SCALE NA SCALE 859 SHELL SIZE : 17 CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOCKET(500 Matings) This document is the property of sOURIAU SOURIAU This document is the property of sOURIAU PLATING : Z = Black Zinc Nickel CONTACT INCK CONTACT LAYOUT : 17-99 FORMAT SOURIAU DRG N° SHEET								
CONTACT TYPE : Standard Crimp Contact ORIENTATION : N SHELL SIZE : 17 CONTACT TYPE : SOCKET(500 Matings) PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 17-99		N		General linear Tolerances:		PRDS / PROJECT		
PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 17-99	CONTACT TYPE : Standard Crimp Contact		TATION : N SOURIAU WWW.SOURIAU.COM SOURIAU it must not be reproduced or					
			FORMAT	SOURIAU			T	
			A3			1/2		

r	Ŧ	െ	н т	m	D	0
		Contact Layout				
4	-x	$\begin{array}{c} +Y \\ & & \\ $				
	B + 131 (3.3) C + 239 (6.07) D305 (7.75) E + .319 (8.10) F + .278 (7.06) G + .189 (4.80) H + .067 (1.70) J067 (1.70) K189 (4.80) L278 (7.06)	Contacts (Insert arrangement 17-99) Contact location V=axis (mm) Contact location X-axis (mm) Y-axis (mm) Y=axis Contact location X-axis (mm) Y-axis (mm) Y-axis (mm) y=321 (8.15) N -336 (7.75) +.099 (2.51) +.293 (7.44) P 239 (6.07) +.214 (5.44) y=23 (7.44) P 239 (6.07) +.214 (5.44) R 131 (3.33) +.293 (7.44) y=0x0 (2.51) O o.707 (1.70) +.177 (4.50) 074 (1.60) 074 (1.60) 034 (0.86) T +.070 (1.78) +.177 (4.50) 260 (6.60) V +.150 (3.81) 075 (1.91) 260 (6.60) V +.150 (3.81) 075 (1.91) 314 (7.96) X 150 (3.81) 075 (1.91) 314 (7.96) X 150 (3.81) 075 (1.91) 260 (6.60) Y 175 (4.45) +.094 (2.39) 161 (4.09) Z +.000 (0.00) +.025 (0.64) 034 (0.86) 034 (0.86)				
ယ	17 00	imber of Size Service Contact position ID 2 16 V,Z MS20053-99 21 20 I All others				
	F					
						SOURIAU shall not be liable for an due to a use of the Products w the Specifications issued by either o (professional recommenda
N						Count FR
					A 18-10-20	PN: 8D517
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Alumi
→					SCALE NA	General linear Tolerances: ±
					SOURIA	U WWW.SOURIAU.
					FORMAT A3	SOURIAU 8D517Z
L	Н	G	F	E	D	C

